	lity									
D:	Indirect heating functionality				No					
Direct heat output(kW)				10,5						
Indirect heat output(kW)				N.A						
			Preferred fuel Model		Emissions from space heating at nominal heat output					
					PM	OGC	СО	NO _x		
Fuel				(Only one)	identifier(s)	[X] mg/N	m ₃ (13 %	0 ₂)		
Wood logs with moisture content \leftarrow 25%				Yes	No	34	16	712	118	
Compressed wood with moisture content < 12%				No	No					
Other woody biomass				No	No					
Anthracite and dry steam coal				No	No					
Hard coke				No	No					
Low temperature coke				No	No					
Bituminous coal				No	No					
Lignite briquettes				No	No					
Peat briquettes				No	No					
Blended fossil fuel briquettes				No	No					
Other fossil fuel				No	No					
Blended biomass and fossil fuel briquettes				No	No					
Other blend of biomass and solid fuel				No	No					
Characteristics when operating with the preferred fuel										
Seasonal space heating er	nergy efficie	ncy η _s [%]		65						
Energy Efficiency Class				Α						
Energy Efficiency Index (EEI)				99						
ltem	Symbol	Value	Unit	lt.	Symbol Value		lue	Unit		
Heat output				Use efficiency (NCV as re		ceived)				
Nominal heat output	P _{nom}	10,5	kW	Useful efficiency at nominal heat output		$\eta_{\text{th, nom}}$	η _{th, nom} 75		%	
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful effic minimum ho output (ind	$\eta_{\text{th, min}}$	N.A.		%		
Auxiliary electricity cons	Type of heat output/room temperature control (select one)									
At nominal heat output	el _{max}	x,xxx	kW	single stag temperatur	no room [yes/no]			ĺ		
At minimum heat output	el _{min}	x,xxx	kW	two or mor	s, no [yes/n		s/no]	Yes		
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room [yes/		s/no]			
				with electro	perature	[yes/no]				
				with electro control plus	perature	[yes/no]				
				with electro control plus	perature	[yes/no]				
				Other cont	nultiple sele	ections p	ossible)			
				room temp presence d	l, with	[yes	s/no]			
				room temp open windo	l, with	rith [yes/no]				
			with distance control option			[yes	s/no]			
Permanent pilot flame po										
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW			1	1			
Contact details	Name and a	address of th	ie supplier:		Brian Ørum, R&I	O Manager, Sca	an A/S, Den	mark		