Indirect heating functiona Direct heat output(kW) Indirect heat output(kW	•			No							
	')			No							
Indirect heat output(kW	')	Direct heat output(kW)				11,4					
	Indirect heat output(kW)				N.A						
			Preferred fuel Model		Emissions from space heating at nominal heat output						
					PM	OGC	CO	NO _x			
Fuel				(Only one)	identifier(s)	[X] mg/Nr	n ₃ (13 %	O ₂)			
Wood logs with moisture content \leftarrow 25%				Yes	No	37	19	699	90		
Compressed wood with moisture content < 12%				No	No						
Other woody biomass				No	No						
Anthracite and dry steam coal				No	No						
Hard coke				No	No						
Low temperature coke				No	No						
Bituminous coal				No	No						
Lignite briquettes				No	No						
Peat briquettes				No	No						
Blended fossil fuel briquettes				No	No						
Other fossil fuel				No	No						
Blended biomass and fossil fuel briquettes				No	No						
Other blend of biomass and solid fuel				No	No						
Characteristics when operating with the preferred fuel											
Seasonal space heating en	ergy efficie	ncy η _s [%]		68							
Energy Efficiency Class				А							
Energy Efficiency Index (EEI)				103							
ltem	Symbol	Value	Unit	lt.	Symbol	Symbol Value		Unit			
Heat output				Use efficiency (NCV as re		ceived)					
Nominal heat output	P_{nom}	11,4	kW	Useful efficiency at nominal heat output		$\eta_{\text{th, nom}}$, _{h, nom} 78		%		
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful effic minimum he output (ind	$\eta_{\text{th, min}}$	N.A.		%			
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)							
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	no room [yes/no]						
At minimum heat output	el _{min}	x,xxx	kW	two or more	s, no [yes/r		/no]	Yes			
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room [yes,		/no]				
				with electro	perature	[yes/no]					
				with electro control plus	perature	[yes/no]					
				with electro control plus	perature	[yes/no]					
				Other cont	nultiple sele	ctions po	ossible)				
				room temp presence d	l, with	[yes	/no]				
				room temp open windo	l, with	th [yes/no]					
D			with distance control option			[yes	/no]				
Permanent pilot flame po											
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW		/	, //	1				
Contact details	ivaine and a	address of th	ie supplier:		Brian Ørum, R&I	Manager, Sca	n A/S, Denm	nark			